

**METHOD FOR REPRESENTING A DIGITAL COLOR
IMAGE USING A SET OF PALETTE COLORS**

CROSS REFERENCE TO RELATED APPLICATIONS

5 Reference is made to commonly assigned U.S. Patent Application
Serial No. _____ filed _____ entitled "Method For Representing s
Digital Color Image Using a Set of Palette Colors Based on Detected Important
Colors" by Jiebo Luo et al., the disclosure of which is incorporated herein by
reference.

FIELD OF THE INVENTION

10 This invention relates to the field of digital imaging, and more
particularly to a method for representing a digital color image using a limited
palette of color values.

BACKGROUND OF THE INVENTION

15 Many color image output devices are not capable of displaying all
of the colors in an input digital image due to the fact that they must be stored in a
memory buffer with a reduced bit-depth. Likewise, it may also be desirable to
represent an image using a reduced bit-depth in order to reduce the amount of
bandwidth needed for the transmission of an image, or the amount of memory
needed to store an image. For example, many computers may use an 8-bit or a
20 16-bit color representation to store an image that is to be displayed on a soft-copy
display such as a CRT or an LCD screen. Such representations allow only 256
and 65,536 unique color values, respectively. This is significantly less than the
16,777,216 possible color values associated with a typical 24-bit color image that
is conventionally used in many digital imaging applications.

25 In applications where it is necessary to represent an input image
using a reduced number of colors, it is necessary to determine the set of colors to
be included in the reduced set of colors. In some cases, a reduced set of colors
may be determined ahead of time independent of the particular image being

INSAIY

09900565-070601

encoded. For example, 3-bits of color information (8 different levels) may be used for the red and green channels of an image, and 2-bits of color information (4 different levels) may be used for the blue channel of an image. This produces a lattice of $8 \times 8 \times 4 = 256$ different color values that can be used to represent the input image using an 8-bit representation. The input digital image can be converted to the 8-bit representation simply by taking the highest 2- or 3-bits of each of the corresponding RGB channels. The result is an image which has quantization errors that can produce visible contours in the image in many circumstances. One disadvantage of this method is that any particular image may not contain colors in all parts of color space. As a result, there may be some of the 256 color values that never get used. Consequently, the quantization errors are larger than they would need to be.

One method for minimizing the visibility of the quantization errors in the reduced bit-depth image is to use a multi-level halftoning algorithm to preserve the local mean of the color value. (For example see: R. S. Gentile, E. Walowit and J. P. Allebach, "Quantization and multilevel halftoning of color images for near original image quality," J. Opt. Soc. Am. A 7, 1019-1026 (1990).)

Another method for minimizing the visibility of the quantization errors in the reduced bit-depth image is to select the palette of color values used to represent each image based on the distribution of color values in the actual image. This avoids the problem of wasting color values that will never be used to represent that particular image. Examples of such image dependent palette selection methods include vector quantization schemes, such as those described in R. S. Gentile, J. P. Allebach and E. Walowit, "Quantization of color images based on uniform color spaces," J. Imaging Technol. 16, 11-21 (1990). These methods typically involve the selection of an initial color palette, followed by an iterative refinement scheme. Another approach, described in R. Balasubramanian and J. P. Allebach, "A new approach to palette selection for color images," J. Imaging

Technol. 17, 284-290 (1991), starts with all of the colors of an image and groups colors into clusters by merging one nearest neighbor pair of clusters at a time until the number of clusters equals the desired number of palette colors. A third class of vector quantization algorithms uses splitting techniques to divide the color space into smaller sub-regions and selects a representative palette color from each sub-region. In general, splitting techniques are computationally more efficient than either the iterative or merging techniques and can provide a structure to the color space that enables efficient pixel mapping at the output. (For a description of several such splitting techniques, see commonly assigned U.S. Patent 5,544,284.)

While vector quantization mechanisms can yield high quality images, they are very computationally intensive. A sequential scalar quantization method is set forth by Allebach et al. in U.S. Patent 5,544,284. This method sequentially partitions a histogram representing the distribution of the original digital color image values into a plurality of sub-regions or color space cells, such that each partitioned color cell is associated with a color in the output color palette. This method has the advantage that it is generally more computationally efficient than vector quantization schemes.

Image dependent palette selection methods have the significant advantage that they assign the palette colors based on the distribution of color values in a particular digital image. Therefore, they avoid the problem of having palette color values that never get used for a particular image. The various methods will generally tend to select palette colors that are representative of the most commonly occurring colors in the particular image. This has the result of reducing the average quantization errors throughout the image. However, in some cases, there may still be large quantization errors in important image regions. For example, consider the case where an image contains the face of a person that only occupies a small image region. The number of pixels in the image that represent

skin-tone colors may be relatively small, and therefore the likelihood that palette colors get assigned to skin-tone colors will be low. As a result, when the image is represented by the set of chosen palette colors, there may be objectionable contours in the face. Since this image region may be very important to an observer, these artifacts may be much more objectionable than they would have been if they had occurred in other image regions. Other types of image content where quantization artifacts may be particularly objectionable would include neutral image regions, and blue sky image regions. Existing image dependent palette selection techniques do not provide any mechanism for minimizing the quantization artifacts in these important image regions unless they are large enough in size to comprise a significant portion of the distribution of image colors.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide an improved method for palette selection which minimizes quantization artifacts for selected important colors.

This object is achieved by a method for converting an input digital color image having a set of possible input colors to an output digital color image having a set of palette colors, the number of palette colors being less than the number of possible input colors, wherein the set of palette colors is determined based on the distribution of colors in the input digital image supplemented by a distribution of important colors. This is accomplished using the steps of determining the distribution of colors in the input digital color image, supplementing the distribution of colors by a distribution of important colors, determining the set of palette colors to be used in the formation of the output digital color image responsive to the supplemented distribution of colors, and forming the output digital color image by assigning each color in the input digital color image to one of the colors in the set of palette colors.

ADVANTAGES

The present invention has the advantage that the set of palette colors that are determined will emphasize important colors whether or not the important colors occupy a large area of the input image. The present method provides more esthetically pleasing images to a viewer.

It has the further advantage that any conventional image-dependent palettization algorithm, such as sequential scalar quantization or vector quantization, can be used in accordance with the present invention by simply appending additional pixels to the input image, where the color of the additional pixels is distributed according to the distribution of important colors.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a flow diagram illustrating the method of the present invention;

FIG. 2 is a diagram showing the process of appending additional pixels to the input digital color image;

FIG. 3 is a diagram showing a multi-level vector error diffusion algorithm; and

FIG. 4 shows an example set of error weights that can be used for a multi-level vector error diffusion algorithm.

DETAILED DESCRIPTION OF THE INVENTION

A flow diagram illustrating the basic method of the present invention is shown in FIG. 1. The method operates on an input digital color image 10 having a set of possible input colors. The set of possible input colors will be defined by the color encoding of the input digital color image 10. Typically, the input digital color image 10 might be a 24-bit RGB color image having $2^{24}=16,777,216$ different colors. However, it will be recognized that the invention is not limited to this configuration. Alternatively, the input digital color image 10 could be at some other bit-depth, or could be in some other color space such as

0990055 070601

YC_RC_B or CIELAB. A determine distribution of input colors step 11 is used to determine the distribution of input colors 12. In a preferred embodiment of the present invention, the distribution of the input colors is determined by forming a three-dimensional histogram of color values.

5 Next, the distribution of input colors 12 is supplemented by a distribution of important colors 13 to form a supplemented distribution of colors 14. A determine set of palette colors step 15 is then used to determine a set of palette colors 16 responsive to the supplemented distribution of colors 14. Since the supplemented distribution of colors 14 has been supplemented by the
10 distribution of important colors 13, the set of palette colors will contain more colors in and/or near the important color regions than would otherwise be the case if the determine set of palette colors step 15 had been applied to the original distribution of input colors 12. The number of colors in the set of palette colors 16 will be less than the number of possible input colors. In a preferred embodiment
15 of the present invention, the number of palette colors will be 256 corresponding to the number of different colors that can be represented with an 8-bit color image. However, it will be obvious to one skilled in the art that the method can be generalized to any number of palette colors. For example, if the output image were a 4-bit color image, the number of corresponding output colors would be 16,
20 or if the output image were a 10-bit color image, the number of corresponding palette colors would be 1024.

 Once the set of palette colors 16 has been determined, an assign palette color to each image pixel step 17 is used to form an output digital color image 18. The output digital color image 18 will be comprised entirely of colors
25 chosen from the set of palette colors. Generally, the palette color for each pixel of the image will be identified by an index value indicating which palette color should be used for that pixel. For example, if there are 256 palette colors used for a particular image, each pixel of the output image can be represented by an 8-bit

0900555-070501
T09070" 59500660

number in the range 0-255. The output digital color image 18 will generally be stored in a digital memory buffer, or in a digital image file. In order to properly display the image, a palette index indicating the color value for each of the different palette colors needs to be associated with the image. When the image is displayed, the palette index can be used to determine the corresponding color value for each of the palette colors.

The steps in the method of FIG. 1 will now be discussed in more detail. The determine distribution of input colors step 11 can take many forms. In a preferred embodiment of the present invention, a three-dimensional histogram of the input colors of the input digital color image is computed. One way that the histogram of input color values can be computed is to go through each pixel of the input image and count the number of occurrences of each input color. To limit the number of bins in the histogram of input colors, ranges of input color values can be grouped into a single bin. For example, instead of 256 different bins for the red dimension, a smaller number of bins such as 32 or 64 could be used.

Additionally, to speed up the computation of the histogram of input colors, it may be desirable to sub-sample the pixels in the input image. For example, instead of examining every image pixel, only the pixels in every 10th row and every 10th column could be used to form the histogram of input colors. In some cases, it might be desirable to convert the image to some other color space before determining the histogram of input colors. For example, an RGB image could be converted to a $Y C_R C_B$ luminance-chrominance representation. This is advantageous for some types of palette determination algorithms. This also makes it possible to use different bin sizes for the luminance and chrominance color channels.

There are many examples of sets of important colors that could be used with the method of the present invention. Generally, the important colors should be chosen or selected to be colors that are of high importance to a human

5
10
15

20

25

Another approach for determining the supplemented distribution of colors 14 is to append additional pixels to the input digital color image to form an enlarged input digital color image. The colors of the additional pixels that are appended to the image are distributed according to the distribution of important colors. The supplemented distribution of colors can then be determined by simply determining the distribution of colors in the enlarged input digital color image. The additional pixels can be provided in the form of a predetermined target image that can be appended to the image. Generally, it may be desirable to resize the target image before appending it to the input digital color image. For example, it will typically be more convenient to combine the two images if the width of the target image is adjusted to match the width of the input digital color image.

This method is illustrated in FIG. 2. An input image 20 is shown which includes a person occupying a relatively small region of the image. A conventional palettization method would assign very little weight to the skin-tone colors since they make up a statistically small portion of the image. However, the colors in the input image are supplemented by appending additional pixels 22 to the image to form an enlarged image 24. The colors of these additional pixels correspond to the distribution of important colors. For example, if the important colors were specified to be skin-tone colors, the additional pixels could include a wide variety of skin-tone colors corresponding to different races, complexions and illuminations of typical skin-tones. The additional pixels could be discrete patches of different skin-tones, or could include smooth gradients covering the range of expected skin-tone colors. The supplemented distribution of colors 14 can then be computed directly from the enlarged image 24, rather than having to combine the distribution of input colors 12 and a separate distribution of important colors 13. When the set of palette colors 16 is determined based on this

supplemented distribution of colors 14, more palette colors will be assigned in the skin-tone region of color space, and therefore the quantization artifacts for these important colors will be reduced.

The advantage of appending additional pixels to the image for the purpose of computing the supplemented distribution of colors 14 rather than simply combining the histogram of important colors and the histogram of input colors is that this method can be implemented without needing to modify the algorithm that is used to determine the set of palette colors. For example, if the algorithm were only available as a compiled executable software module, then it would be possible to practice the method of the present invention by simply including a pre-processing step of appending the additional image pixels to the input image before running the software module, and a post-processing step to strip the additional pixels off of the processed output image created by the software module.

There are many different methods that could be used for the determine set of palette colors step 15. In a preferred embodiment of the present invention, a sequential scalar quantization technique such as that described by Allebach et al. in U.S. Patent 5,544,284 is used. This approach works by sequentially partitioning the colors of the supplemented distribution of colors 14 into a set of color space regions. This is generally done on a luminance-chrominance representation of the image. The set of palette colors 16 is then determined by selecting an output color for each color space region in the set of color space regions. For more details of this method, reference should be made to the above-mentioned U.S. Patent 5,544,284.

Other methods that could be used for the determine set of palette colors step 15 include a wide variety of vector quantization techniques. Several examples of these methods are discussed in U.S. Patent 5,544,284. It will be obvious to one skilled in the art that the method of the present invention can easily

09900555-070601
F09020" 59500660

be used with any image palettization technique where the selected palette colors are dependent on the distribution of colors in the input image.

Once the set of palette colors 16 is determined, the assign palette color to each image pixel step 17 is used to form an output digital color image 18.

- 5 One manner in which this step can be implemented is to determine the palette color having the smallest color difference relative to the color of each pixel of the input digital color image.

- 10 In some cases, a particular input digital color image 10 might not contain any of the colors in the distribution of important colors 13. As a result, the method of the present invention would result in assigning palette colors that would never get used in output digital color image.18. In a variation of the present invention, a test can be first applied to the input digital color image 10 to determine if it contains any colors in the distribution of important colors 13. If there are no such colors, then the step of forming the supplemented distribution of colors 14 can be skipped, and the set of palette colors can be determined directly from the distribution of input colors 12. One convenient means for determining whether the input digital color image 10 contains any colors in the distribution of important colors 13 is to examine the distribution of input colors 12. For example, if a three-dimensional histogram were used to represent the distribution of input colors 12, then it would simply be necessary to examine the histogram cell(s) corresponding to the colors in the distribution of important colors. If these histogram cell(s) were all found to contain zeros, then it can be concluded that the input digital color image 10 does not contain any colors in the distribution of important colors 13. If there are multiple subsets of important colors in the distribution of important colors 13 (for example skin-tones and neutrals), then only the subset(s) of important colors that are present in the distribution of input colors 11 need to be used to form the supplemented distribution of colors 14. In this case, the distribution of important colors is only used to supplement the

090056 070601

distribution of colors in the input digital color image in important color regions where the input digital color image contains a significant number of pixels.

In a variation of the present invention, the assign palette color to each image pixel step 17 includes the application of a multi-level halftoning algorithm. Multi-level halftoning algorithms can be used to create the appearance of color values intermediate to the palette colors by varying the palette values assigned to the pixels of the output digital color image 18 such that the local mean color value is approximately preserved. An example of a multi-level halftoning method that could be used would be multi-level vector error diffusion. A flow diagram illustrating a typical multi-level vector error diffusion algorithm is shown in FIG. 3. In this figure, an input pixel color value I_{ij} from the i^{th} column and j^{th} row of the input digital color image 10 is processed by an assign palette color to each image pixel step 17 to form a corresponding output pixel color value O_{ij} of the output digital color image 18. The assign palette color to each image pixel step 17 introduces a quantization error due to the fact that the output pixel value is selected to be one of the palette colors in the determined set of palette colors 16. A difference operation 30 is used to compute a color error E_{ij} representing the vector difference between the input pixel color value I_{ij} and the output pixel color value O_{ij} . A weight errors step 32 is used to apply a series of error weights W_{ij} to the resulting color error E_{ij} . A sum operation 34 is then used to add the weighted color errors to nearby input pixels that have yet to be processed. An example set of error weights W_{ij} is shown in FIG. 4. In this example, the color error E_{ij} for the current pixel 40 with column and row address (i, j) is weighted by a factor of $1/4$ and distributed to the next pixel to the right 42 in the current row of the image having the column and row address $(i+1, j)$. Likewise the color error E_{ij} is also weighted by factors of $1/4$ and distributed to three pixels in the next row of the image 44 having column and row addresses $(i-1, j+1)$, $(i, j+1)$ and $(i+1, j+1)$. In this way, the quantization errors introduced when processing the current pixel 40

09900565 "070604

are distributed to nearby input pixels that have not yet been processed. The result is that the local mean color value is approximately preserved.

A computer program product may include one or more storage medium, for example; magnetic storage media such as magnetic disk (such as a floppy disk) or magnetic tape; optical storage media such as optical disk, optical tape, or machine readable bar code; solid-state electronic storage devices such as random access memory (RAM), or read-only memory (ROM); or any other physical device or media employed to store a computer program having instructions for controlling one or more computers to practice the method according to the present invention.

The invention has been described in detail with particular reference to certain preferred embodiments thereof, but it will be understood that variations and modifications can be effected within the spirit and scope of the invention.

09900565 "070601

PARTS LIST

10	input digital color image
11	determine distribution of input colors step
12	distribution of input colors
13	distribution of important colors
14	supplemented distribution of colors
15	determine set of palette colors step
16	set of palette colors
17	assign palette color to each image pixel step
18	output digital color image
20	input image
22	additional pixels
24	enlarged image
30	difference operation
32	weight errors step
34	sum operation
40	current pixel
42	next pixel to the right
44	pixels in next row of image

09900565-070604